



Tracker168



Net168

2 POS
Integration



All ROM Cash Registers

4 POS
Integration



All WEPOS Cash Registers

Text Overlay

SUB TOTAL	8300.00
DISCOUNT	.00
TOTAL SALES	8300.00
STATE SALES TAX	581.00

TOTAL	8881.00
CASH	8900.00
CHANGE	19.00

10 Configurable
Searching Indexes



Remote Viewing
(Up to 128 DVRs)



3i CCTV
iP integration, intelligent

Telexper International Inc.

3F.-3, No. 2, Jian 8th Rd., Zhonghe Dist.,
New Taipei City 235, Taiwan (R.O.C.)

Tel : +886-2-6620 5898

Fax: +886-2-6620 6909

E-mail: sales@telexper.com



ISO 9001:2008

Headquarters

333235 Transit Avenue,
Union City, CA 94587 U.S.A.

Tel : +1.510.477 9150

Fax: +1.510.477 9644

Email: sales-us@telexper.com

www.telexper.com

CE FC RoHS Onvif

OEM/ODM
Project Support

POS DVR

Specification

Model nr	Net168		Tracker168
Operation system	WinXP Embedded (stored in DOM Module)		
Codec	Proprietary M-JPEG + Wavelet		
Watch Dog Timer	Hardware		
Video - Video input	x 4	x 8	x 16
- Loop through	x 4	N/A	x 16
- VGA output	x 1	x 1	x 1
- Sequential output (composite)	N/A	N/A	x 4
Audio - Input	Optional		
- Speaker out	Optional		
Alarm Input	Dry contact x4	Dry contact x8	Dry contact x 16
Control output	x 1	x 1	x 1
RS232 interface	x 2	x 2	x 2
TCPIP (internet)	RJ45 x 1	RJ45 x 1	RJ45 x 1
Hot Standby REC	Yes (valid for more than two HDDs configuration ONLY)		
Redundancy REC	Yes (valid for more than two HDDs configuration ONLY)		
Display rate (max) - Spot mode	120 f/s		120 f/s
- Divided mode	60 f/s		120 f/s
Display resolution (max)	640 x 480 pixels		
Recording rate (max.)	60 f/s		120 f/s
Recording resolution (max.)	640 x 480 pixels		
Recording quality	Low, Fair, Good, Better, Best		
Compression ratio	600:1 (1.5kB)		
Nr of installed hard disk (IDE Type, max)	x 2 (160/250/ 500 GB)		x 3 (160/ 250/ 500 GB)
Water Mark	Yes		
Built-in CD Writer for AVI Export	Optional		Optional
AVI export media	CD Writer, external USB memory stick & etc..		
System alarm	Video Loss, Motion, External Alarm		
PTZ Control	Pelco, Panasonic, Kalatel, Bosch & others.		
Power source	90 to 264Vac, 50/60 Hz Switching		
Power consumption	< 50 W	< 50 W	< 185 W
Weight	Net:13.23 LB(6kg), Gross:17.64LB(8kg)		Net:33.07LB(15kg), Gross:41.89LB(19kg)
Dimension	335x435x45 (mm) 13.18x17.13x1.77 (inch)		473x430x111 (mm) 18.62x16.93x4.37 (inch)
Approval	CE, FCC		

Specifications are subject to change without prior notice



Telexper International Inc.
 3F.-3, No.2, Jian 8th Rd., Zhonghe Dist.,
 New Taipei City 235, Taiwan (R.O.C.)
 Tel : +886-2-6620 5898
 Fax: +886-2-6620 6909
 E-mail: sales@telexper.com



Headquarters
 333235 Transit Avenue,
 Union City, CA 94587 U.S.A.
 Tel : +1.510.477 9150
 Fax: +1.510.477 9644
 Email: sales-us@telexper.com

www.telexper.com
 CE FC RoHS Onvif
OPEN/ODM
Project Support