

Network Commander Station (for ATM Application)



What Telexper NVR can do for your ATM application?

- Fight against financial fraud activities
- Make sure eligible ATM cardholder perform normally and safe transactions on ATM
- Help bank has real-time and accurate information of ATM operation
- Guard against vandalization to ATM
- Reduce the disputes between ATM cardholder and bank
- Record the image of cardholders while processing transactions on ATM to fight against fraud identity
- Provide the recording data for investigation in case of crime
- Chosen by worldwide ATM manufacturers (e.g. NCR, WinCor-Nixdorf, Hitachi and more) as the DVR supplier.

Main Features:

- Embedded Windows 7 OS on SSD for higher and stable performance
- H.264 & M-JPEG dual video compression
- Plug & Play, no configuration needed
- Video processing, live monitoring, playback, backup and remote viewing.
- Support 16 IP cameras
- Card number imprinted on the recorded video images
- Fast and easy in searching transaction
- 4 hard drives model and supports RAID-05



nCS-16 4HDD

Hardware Specifications:

Model No.:	nCS-16
	16ch Commander Station Basic
Electrical:	
Operating System	Windows 7 Embedded OS
TCP/IP	Gigabit Port (RJ-45)
Video Inputs	IPx16
Audio Recording	IPx16
Live Display	320x240 / 360x240 / 640x480 / 720x480 / 1280x720 / 1280x1024 / 1600x1200 / 1920 x 1080 / 2048 x 1536
Playback Rate	Max. 480 fps @ D1
Rec. Resolution	320x240 / 360x240 / 640x480 / 720x480 / 1280x720 / 1280x1024 / 1600x1200 / 1920 x 1080 / 2048 x 1536
Picture Quality	High/Normal/Low
Storage Hard Drive	3.5" SATA type x 4 (2TB or 3TB or 4TB)
Support RAID-05	Yes
Alarm Notifications	Video Loss, Disconnection, HDD, Motions, Sensors, I/O Devices
PTZ Control	Pelco D, Pelco P, Panasonic, Kalatel, Bosch & etc
Power Requirements:	
Power Input	90-240 Vac, 50/ 60 Hz
Mechanical:	
Enclosure	Metal Material
Dimension (L x W x H)	445 x 430 x 155 mm
Weight	10 Kgs (without HDD)
Environment:	
Operation Temp.	0 to 50 °C, 10% to 80% R.H.
Storage Temp.	(-)10 to (+) 70 °C, 5% to 95%
Certifications:	CE, FCC, RoHS

Telexper International Inc.

33235 Transit Avenue, Union City, CA 94587 USA / Phone: 1-510-477-9150 / Fax: 1-510-477-9634

3F-3, No.2, Jian 8th Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.) / Phone: +886-2-6620-5898 / Fax: +886-2-6620-6909 / <http://www.telexper.com> / E-mail: sales-tw@telexper.com

Full Software Functions:

General
<ul style="list-style-type: none">● Multi Video streaming design<ul style="list-style-type: none">- Supports 16 IP cameras- Supports Static IP and Dynamic IP
Video
<ul style="list-style-type: none">● Compatible with multi-codec, multi-brands IP products<ul style="list-style-type: none">- M-JPEG, MPEG4, H.264 supported● Multiple Steaming
Live & Recording
<ul style="list-style-type: none">● Powerful Live Monitoring<ul style="list-style-type: none">- Group view- 30fps @ 1920*1080P resolution per every IP camera- 20fps @ 2048*1536 resolutions per every IP camera- 1/4/9/10/13/16/18 cameras display on screen● User-friendly system configuration of REC such as<ul style="list-style-type: none">- Recording Schedule- Frame rate (fps) & quality (compression & bit rate) adjustment- Multi-channel of video & audio REC- ATM card transaction recording- Auto recycle recording files when storage is full● Snap shot of Live images
Playback
<ul style="list-style-type: none">● Intelligent search playback (built-in indexed database)<ul style="list-style-type: none">- Date/Time search- Motion search (up to four adjustable detection zones)- Smart search: Missing Object, foreign object search- Alarm search- Card number search (with ATM/Access Control/POS integration function)
Alarm
<ul style="list-style-type: none">● Alarm Call Live Monitoring<ul style="list-style-type: none">- Pre-recorded digital alert message per every device● User-friendly Alarm E-mail Notification
Others
<ul style="list-style-type: none">● Automatic switch from bad track of HDD without interrupting recording

Specifications are subject to change without prior notice.