

Full HD 8MP IP Vandal-Proof Dome Camera



Future-proof Technology

The IP cameras series with mechanical IR cut and day/night capability supports color at day and black & white at night. This all-in-one-design camera series are very versatile. It supports PoE (Power over Ethernet), so there is no need for external power supply. Options of fixed lens, manual and zoom vari-focal are available for different environments.

It provides round-the-clock, high quality H.265 video with Internet Protocol. Its remote monitoring applications allow homeowners and businesses to view their camera(s) through any internet connection available through a computer or a 3G phone.

The Dome camera can be mounted almost anywhere using a variety of dome mounts, such as pendant and recessed mounts.

Features:

- 1/2.8" CMOS Progressive Scan
- Resolution of 3840x2160 @15fps
- PoE (IEEE802.3af, Power over Ethernet)
- True Day and Night (Mechanical IR Cut Filter, IR LED)
- Built-in Manual Vari-Focal or Zoom Lens.
- H.265/H.264/MJPEG (SOC) Video compression
- Built-in hardware motion detection
- Alarm Input x 1
- Two-way audio communication over IP networks
- Multi streaming
- User-friendly GUI and no configuration is required
- Excellent heat dissipation
- High power IR LED



nCam-P2336/xx
nCam-P2346/xx



Optional Bracket

Telexper International Inc.

33235 Transit Avenue, Union City, CA 94587 USA / Phone: 1-510-477-9150 / Fax: 1-510-477-9634

3F.-3, No.2, Jian 8th Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.) / Phone: +886-2-6620-5898 / Fax: +886-2-6620-6909 / <http://www.telexper.com> / E-mail: sales-tw@telexper.com

Specification

Model	nCam-P2336/xx	nCam-P2346/xx
Image Sensor	1/2.8" CMOS Progressive Scan	
Resolution & Rate	3840x2160 @ 15fps	
Video Codec	H.265/H.264/M-JPEG hardware (SOC) compression	
Video Stream	H.265/H.264, Multiple Streams	
Video Bit Rate	30K- 6M bps	
Sensitivity	0.1 Lux @ F1.4 (IR LED off) / 0 Lux @ F1.4 (IR LED On)	
S/N Ratio	> 63 dB	
Electronic Shutter	1/5 to 1/30000 sec..	
Flicker less	Yes, 1/120 sec.(60Hz) 1/100 sec.(50Hz)	
Exposure	Automatic	
Back Light Compensation	Automatic	
AGC	Automatic	
White Balance	Automatic	
Motion Detection	Yes, 4 different areas (hardware)	
Picture Resolution	3840x2160	
Lens	Manual Vari-Focal 2.8 mm ~ 12 mm	Zoom Lens 6 mm ~ 22 mm / 2.7 ~ 13.5 mm
Video Adjustment	Contrast, Brightness, Saturation, Sharpness	
Day/Night	Yes, Mechanical IR Cut Filter	
IR Led	High Power IR LED x 2	
IR Sensitivity	700nm to 1100nm	
IR Distance	20 meters	
GPIO	Alarm in x 1	
Control Interface	RS-485	
2-Way Audio	Yes, (Audio In x1, Audio Out x1)	
Operation System	Linux Embedded	
Processor	ARM 9 ,32 bit RISC	
Security	ID / Password	
Firmware Update	Yes, Remotely	
Watch Dog Timer	Yes	
Network Interface	RJ-45 (10/ 100 Base-T)	
Protocol	HTTP, TCP/ IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, RTSP/RTP, TMSP	
Power Requirement	PoE (IEEE802.3af) or 12VDC	
Power Consumption	9W with Higher Power Led ON	9.5W with Higher Power Led ON
Operating Temperature	-20℃ to 50℃, -4°F to 122°F	
Operation Humidity	5%--95%	
Storage	-30℃ to 70℃, -22°F to 158°F	
Outdoor	Yes, IP66	
Dimension (Φ x L)	144 x 115 mm	
Certifications	CE, FCC, RoHS	

TMSP: Telexper Multiple Stream Protocol
(Specifications subject to change without prior notice)

Telexper International Inc.

33235 Transit Avenue, Union City, CA 94587 USA / Phone: 1-510-477-9150 / Fax: 1-510-477-9634

3F.-3, No.2, Jian 8th Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.) / Phone: +886-2-6620-5898 / Fax: +886-2-6620-6909 / <http://www.telexper.com> / E-mail: sales-tw@telexper.com